



# MOTO ATV 4T 10W40

## Description

It is the most suitable completely synthetic lubricant oil for all kinds of quads and ATV's. It has been tested in the most extreme situations while driving the engine beyond its limits. Furthermore, and among other characteristics, it guarantees excellent thermal stability and resistance to wear in engines with oil bath clutches.

## Properties

- Its synthetic composition has been especially reinforced to sustain conditions normally experienced by all-terrain vehicles and quads
- Its excellent thermal stability and good resistance to oxidation facilitates high engine performance under any temperature
- It is especially designed for use in conditions withstanding high engine revolutions, offering excellent advantages for this kind of all-terrain vehicle in sports settings.
- Provides good friction on clutch discs, preventing slippage and premature wear in joint engine and transmission (wet clutch) lubrication systems

## Quality level

- API SJ
- JASO T 903:2006 MA & MA2

## Technical Characteristics

	UNIT	METHOD	VALUE
SAE Grade			10W40
Density at 15°C	g/ml	ASTM D 4052	0.854
Viscosity at 100°C	cSt	ASTM D 445	14.9
Viscosity at 40°C	cSt	ASTM D 445	96
Viscosity at -25°C	cP	ASTM D 5293	7000 max
Viscosity rate	-	ASTM D 2270	160 min.
Flash point, open cup	°C	ASTM D 92	238
Pour point	°C	ASTM D 97	-27
TBN	mg KOH/g	ASTM D 2896	6.6
Sulphated ashes	% in weight	ASTM D 874	0.8
Bosch Injector Shearing: Viscosity at 100°C after shear	cSt	CEC-L014-93	12.8

## ■ Hazard Identification

---

This product is not classified as toxic or hazardous under current legislation.

## ■ Handling

---

Minimum precautions should be taken to avoid prolonged contact with the skin. The use of gloves, visors or glasses is recommended to avoid splashes.

## ■ Health and safety hazards

---

**Inhalation:** Given that it is not a particularly volatile product, the risk of inhalation is minimal.

**Ingestion:** Do not induce vomiting. Supply water. Seek medical advice.

**Contact with the skin:** Wash thoroughly with soap and water.

**Eyes:** Wash thoroughly with water.

**General measures:** Seek medical advice.

## ■ Fire-extinguishing measures

---

No special measures required.

**Fire-extinguishing measures:** Foams, dry chemicals, CO<sub>2</sub>, water spray. Do not apply the jet of water directly as this could cause the product to disperse.

## ■ Environmental precautions

---

Danger of physical pollution if spilt (watercourses, coastlines, soil, etc.) due to its floatability and oily consistency that may harm flora and fauna on contact. Avoid material getting into water outlets.

**Decontamination and cleaning:** Treat as an accidental oil spillage. Prevent dispersion using mechanical barriers and remove by physical or chemical means.

A safety information file is available on request.

repsol.com

Unless otherwise indicated, the figures cited in technical characteristics should be considered typical.

---

Technical data sheet for Lubricants. Review 2 October 2010.